




		W	K	mA	Lm	%Eff
SALT PC 3	A220-03- 1 -1- TW TN	23,5W	3000K	700	2850	78%
	A220-03- 1 -2- TW TN	23,5W	4000K	700	3000	78%
SALT PC 4	A220-04- ② -1- TW TN	34,5W	3000K	1050	4450	78%
	A220-04- ② -2- TW TN	34,5W	4000K	1050	4700	78%
SALT PC 5	A220-05- ③ -1- TW TN	47,5W	3000K	1200	5900	78%
	A220-05- ③ -2- TW TN	47,5W	4000K	1200	6200	78%
SALT PC 6	A220-06- ④ -1- TW TN	60,5W	3000K	1050	7550	78%
	A220-06- ④ -2- TW TN	60,5W	4000K	1050	8000	78%



LED | 220V/240V 50/60 Hz | CE | IP20 | IK07 | CRI>80

OPTIONS* | INCL | ELEC | CABLE 2 m | FAST | 91° | 1

② OPTIONS*

2	DIM Push
3	DIM 1-10V
4	DIM DALI

COLOUR | TW | TN

MATERIAL | AL | PC | PMMA

5,1 Kg

452x452x418 mm



TW



TN

SALT PC 3000 K

LED 91° | 3000 K

C90 - C270 105° 90° 75° 60° 45° 30° 15° 0° adr/Klm η = 78%	23,5 W				34,5W				47,5 W				60,5 W			
	h (m)	d (m)	Emed (lux)	Emax (lux)	h (m)	d (m)	Emed (lux)	Emax (lux)	h (m)	d (m)	Emed (lux)	Emax (lux)	h (m)	d (m)	Emed (lux)	Emax (lux)
CIE η L: 0.78 54-82-96-100-79 DIN A40 UTE 0.78 D + 0.00 T CIBSE BZ 4	1	2.07	416	831	1	2.07	650	1298	1	2.07	861	1721	1	2.07	1102	2202
	2	4.14	104	207	2	4.14	162	324	2	4.14	215	430	2	4.14	275	550
	3	6.21	46	92	3	6.21	72	144	3	6.21	95	191	3	6.21	122	244
	4	8.27	26	51	4	8.27	40	81	4	8.27	53	107	4	8.27	68	137

SALT PC 4000 K

LED 91° | 4000 K

C90 - C270 105° 90° 75° 60° 45° 30° 15° 0° adr/Klm η = 78%	23,5 W				34,5W				47,5 W				60,5 W			
	h (m)	d (m)	Emed (lux)	Emax (lux)	h (m)	d (m)	Emed (lux)	Emax (lux)	h (m)	d (m)	Emed (lux)	Emax (lux)	h (m)	d (m)	Emed (lux)	Emax (lux)
CIE η L: 0.78 54-82-96-100-79 DIN A40 UTE 0.78 D + 0.00 T CIBSE BZ 4	1	2.07	438	875	1	2.07	686	1371	1	2.07	905	1808	1	2.07	1168	2333
	2	4.14	109	218	2	4.14	171	342	2	4.14	226	452	2	4.14	292	583
	3	6.21	48	97	3	6.21	76	152	3	6.21	100	200	3	6.21	129	259
	4	8.27	27	54	4	8.27	42	85	4	8.27	56	113	4	8.27	73	145